

Touchless Faucet Deck Mounted

TLE26001D

eatures

- Hands-free usage increases hygiene
- Sensor positioned underneath the spout • head for more accurate user detection
- SELF POWER Technology: Self-generated power saves electricity (Controller: TLE03501H)
- WATER SAVING
- ECO CAP Technology: TOTO aerated bubble technology adds air to the water to achieve full water jet

Specifications

Flow Rate: 1.3L/min Water Pressure: 0.05MPa ~ 0.75MPa Finish:

Nickel Chrome

Parts description

Single Supply Combination

- AC Controller 1. TLE26001D (Deck-mounted) 2. TLE01501H (AC Operated - BF Plug) 3. *TLN01102A (Stop Valve Set)**
- Self Powered Controller 1. TLE26001D (Deck-mounted) 2. TLE03501H (Self Powered) 3. *TLN01102A (Stop Valve Set)**
- Battery Operated Controller 1. TLE26001D (Deck-mounted) 2. TLE04501H (Battery Operated) 3. TLN01102A (Stop Valve Set)* •

NOTE

*For Thermostatic Please purchase TLE05701A (Thermostat) and TLN01103A (Stop Valve Set) instead 0

Certifications



eddot winner 2021 Single Supply 130 ①TLE26001D 205 ŝ 115 13 Sensor Cord (L=980) Hole 35±2 Max30 Hose (L=800) 2 Refer to types of Controller AC Plug Power Cord 105, 112 (L=750mm) 116 8 Ŧ 47 34 G1/2 70 120 3TLN01102A Ľ ()Recommended Dimension

10052024

TOUCHLESS FAUCET

